



Protea Srl Unipersonale: Legal head office via Marco Polo, 127/12 55049 Viareggio
Headquarters: via Scirocco 53, Int. 34 55049 Viareggio (LU)
info@proteasrl.com www.proteasrl.com



Fig.1

**EQUIPPED WITH SUPPORT
FOR SPARE BATTERY SO AS
TO DOUBLE THE
AUTONOMY.**

OTHER APPLICATIONS:

- Sanitizing washing of surfaces and floors
- Sanitization of work tops and tools
- Sanitizing washing of cold rooms and wineries as well as recipients

OZOSPRAY

BACKPACK SPRAYER
FOR THE NEBULIZATION OF OZONATED WATER

OZOSPRAY is a system that produces ozonated water inside a 12 liter tank. The system is powered by a Makita or similar rechargeable lithium battery (18V – 6Ah). The sanitizer thus produced is sprayed at a pressure of 2-4 bar by a manual pump made of plastic and ozone-resistant materials.

Water mixed with Ozone (O_3) is a highly sanitizing product and is useful for killing bacteria, mould, fungi, spores, etc. The same can also be used to significantly reduce the presence of insects, parasites, aphids, arachnids, etc.

With **OZOSPRAY** system it is possible to obtain excellent results and many benefits with a limited cost over time.

TECHNICAL INFORMATION

SUBJECT	SPECIFICATIONS
POWER SUPPLY	Lithium battery 18V 6Ah (MAKITA BL1860B)
AUTONOMY	1,5 hours
DIMENSIONS	440x470x230 mm
OZONE	1 ppm*
WEIGHT	5 Kg (empty tank)
PRESSURE	2-4 bar
TANK CAPACITY	12L

* Tests carried out with clean water at a temperature between 15°C and 20°C.

OZONE PECULIARITIES

After fluoride, Ozone is the strongest oxidant present in nature; for this reason, it is also an energetic sanitizing agent. Being an unstable gas, ozone has a very short life span (about half an hour) in natural conditions: this is the reason why it cannot be stored in tanks. After completing its sanitizing action, it reverts back to oxygen without leaving any residual agents in environment and in water.

The sanitizing property of Ozone and its reactivity are superior to any other system used.